



# Remote Cargo Hook Test Form

## C250

Work Order \_\_\_\_\_

Customer \_\_\_\_\_

Serial Number \_\_\_\_\_

Date \_\_\_\_\_

# of Releases	Load (Lbs.)	Release Method	Remarks	Result	Pass/fail
1	62,500	Static Hold	Hold for two Minutes and reduce load to zero	N/A	
10	12,500	Electircal, 25 volts	No "hang ups" permitted	N/A	
2	25,000	Electircal, 22 volts	Current shall not exceed 14.8A	Amp.	
2	20,000	Electircal, 22 volts	Current shall not exceed 14.8A	Amp.	
2	15,000	Electircal, 22 volts	Current shall not exceed 14.8A	Amp.	
2	10,000	Electircal, 22 volts	Current shall not exceed 14.8A	Amp.	
2	500	Electircal, 22 volts	Current shall not exceed 14.8A	Amp.	
1	25,000	Electircal, 20 volts	Current shall not exceed 14.8A	Amp.	
1	25,000	Electircal, 28 volts	Current shall not exceed 14.8A	Amp.	
1	25,000	Manual		N/A	
1	25,000	Impact Test	Impact shackle 10 times, shall not release	N/A	
1	N/A	Solenoid Ohms	Shall not exceed 1.8-2.3 Ohms	Ohms	
1	N/A	Electircal Continuity	Across both wires	N/A	

Test Conducted By \_\_\_\_\_

Signature: \_\_\_\_\_